



## RSL

Rock shredder - Stone crusher - Soil stabilizer and Asphalt grinder\* for tractors between 80 and 190 HP with a working depth of 27 cm.

**Standard equipment:** PTO driveshaft with cam clutch, hydraulic adjustable skids, HARDOX® counter blades, inner bolted HARDOX® plates for a complete anti-wear protection, bolted grid on rear hood, forged tool holders made of heat treated steel, oversized rotor bearings, „double steel cage system“ machine shell (WELDOX® steel) to provide an effective protection against dust, structural steel outside and wear resistant steel inside, rear hydraulic protection/dozing hood for a better regulation of the output material, bolted forged rotor axles. One side gearbox transmission (540 rpm) or with double side gearbox transmission (and 1000 rpm PTO).

**Options:** hydraulic top link, water spray system. Possibility to have the rotor equipped with tooth type “G/3”.

**Notes:** For the correct usage, a creeper gear transmission is recommended.



## RSL

Model	Tractor HP Min Max	PTO rpm	Working width mm	Overall width mm	Weight Kg	Working depth mm (max)	Teeth q.ty/type R + R/HD	Teeth q.ty/type G/3+H
RSL 100	80 - 120	540	1000	1435	1600	150 - 270	58 + 16	32+4
RSL 125	90 - 120	540	1240	1675	1800	150 - 270	82 + 16	40+4
RSL 150	100 - 120	540	1480	1915	1960	150 - 270	98 + 16	48+4

## RSL/DT

Model	Tractor HP Min Max	PTO rpm	Working width mm	Overall width mm	Weight Kg	Working depth mm (max)	Teeth q.ty/type R + R/HD	Teeth q.ty/type G/3+H
RSL/DT 175	120 - 190	1000	1720	2065	2350	150 - 270	122 + 16	58+4
RSL/DT 200	130 - 190	1000	1960	2305	2500	150 - 270	138 + 16	66+4
RSL/DT 225	140 - 190	1000	2200	2545	2650	150 - 270	154 + 16	76+4

Data refers to the machine without options.

\*in specific condition



Tooth type R/65



Tooth type R/HD 65  
(option)



Tooth type R/44  
with adaptor G/3  
(option)



Tooth type G/3  
(option)



Tooth type G/3/R44  
+ adaptor G/3  
(option)



Tooth type R/HD 65  
(side scraper)



Tooth type H  
(side scraper)