



STCH STCH/HD

Stone crushers with a max working depth of 10 inches for tractors between 180 and 300 HP.

Standard equipment: double driven transmission, PTO driveshaft with cam clutch, gearbox with freewheel, adjustable skids with interchangeable ploughshares and skid shoes, hydraulic rear hood, adjustable counter blade. In addition, for the

STCH/HD model: PTO driveshaft without cam clutch, inner plates in Hardox steel, adjustable three point linkage, teeth type STC/3/HD.

Options: dozing blade, road kit, hydraulic top link, possibility to have the rotor equipped with tooth type "STC/3/HD" or "STC/3/FP".

Notes: For the correct usage, a creeper gear transmission is recommended.



STCH

Model	Tractor HP Min	Tractor HP Max	PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Working depth inches (max)	Teeth q.ty/type STC/3+STC/3/HD
STCH 200	180	280	1000	82	100	9481	20	10	52+4
STCH 225	200	280	1000	91	110	10010	20	10	58+4
STCH 250	220	280	1000	101	119	10540	20	10	66+4

STCH/HD

Model	Tractor HP Min	Tractor HP Max	PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Working depth inches (max)	Teeth q.ty/type STC/3/HD
STCH-HD 225	200	300	1000	91	110	10518	20	10	62
STCH-HD 250	220	300	1000	101	119	11290	20	10	70

Data refers to the machine without options.



Tooth type STC/3



Tooth type STC/3/HD (option)



Tooth type STC/3/FP (option)



Tooth type STC/3/HD (side scraper)