



UML/DT

Forestry mulcher with fixed teeth rotor for tractors between 80 and 130 HP.

Standard equipment: PTO driveshaft with cam clutch, gearbox with freewheel, hydraulic rear hood, adjustable skids, "Anti dust" machine body.

Options: hydraulic top link, mechanic or hydraulic push frame, special skids to go underground, possibility to have the rotor equipped with tooth type C/3/HD, type K, blade C/3 or type I.

Notes: For the correct usage, creeper gear transmission and reversible driving console are recommended.



UML/DT

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type C/3+C/3/SS	Teeth q.ty/type I+C/3/SS
UML/DT 200	80	130	1000	2060	2380	1500	250	42+2	58+2
UML/DT 225	90	130	1000	2300	2620	1600	250	46+2	66+2

Data refers to the machine without options.



Tooth type C/3
(standard)



Tooth type C/3/HD
(option)



Tooth blade type C/3
(option)



Tooth type K
(option)



Tooth type I
(option)



Tooth type C/3/SS
(side scraper)

The technical data are indicative, not binding and are subject to modification without prior notice.