



## UML/LOW

Forestry mulcher with fixed teeth rotor for tractors between 60 and 110 HP.

**Standard equipment:** PTO driveshaft with cam clutch, gearbox with freewheel, hydraulic rear hood, adjustable skids.

**Options:** hydraulic top link, special skids to go underground, push frame, possibility to have the rotor equipped with tooth type C/3/HD, type K, blade C/3 or type I.

**Notes:** For the correct usage, creeper gear transmission and reversible driving console are recommended.



Especially developed for tractors with low three point hitch (e.g. crawler tractors).



## UML/LOW

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width mm	Overall width mm	Weight Kg	Grinding diameter mm (max)	Teeth q.ty/type C/3+C/3/SS	Teeth q.ty/type I+C/3/SS
UML/LOW 150	60	100	540	1580	1840	930	200	32+2	42+2
UML/LOW 175	70	110	540	1820	2080	1060	200	36+2	50+2
UML/LOW 200	80	110	540	2060	2380	1190	200	42+2	58+2

Data refers to the machine without options.



Tooth type C/3  
(standard)



Tooth type C/3/HD  
(option)



Tooth blade type C/3  
(option)



Tooth type K  
(option)



Tooth type I  
(option)



Tooth type C/3/SS  
(side scraper)

The technical data are indicative, not binding and are subject to modification without prior notice.