



UMM/DT

Forestry mulcher with fixed teeth rotor for tractors between 140 and 240 HP.

Standard equipment: PTO driveshaft with cam clutch, gearbox with freewheel, self-ranging system of the PTO drive shaft gearbox type "Z", hydraulic rear hood, centralized greasing hub, adjustable skids, counter blades and inner plates screwed from outside.

Options: mechanic or hydraulic guard frame, available with extra ripper teeth, special skids to go underground, third line counter blades, W-style self-aligning device between gearbox and PTO, possibility to have the rotor equipped with tooth type C/3/HD, type K, blade C/3 or tooth type I.

Notes: For the correct usage, creeper gear transmission and reversible driving console are recommended.



UMM/DT

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty/type C/3+C/3/SS	Teeth q.ty/type I+C/3/SS
UMM/DT 200	140	240	1000	82	97	4800	12	42+2	58+2
UMM/DT 225	150	240	1000	91	107	5350	12	46+2	66+2
UMM/DT 250	160	240	1000	100	116	5500	12	52+2	74+2

Data refers to the machine without options.



Tooth type C/3
(standard)



Tooth type C/3/HD
(option)



Tooth blade type C/3
(option)



Tooth type K
(option)



Tooth type I
(option)



Tooth type C/3/SS
(side scraper)